


# MOCCA S PRO

“Mocca - The all-in-one cylindrical solution. Mocca is our interpretation of an all integrated cylindrical spotlight. The cooling is passive, being all silent, by allowing cold air to flow from the middle of the cylinder and out in the back. By choosing Mocca you will get a uncluttered environment focusing on the essential: The simplicity of the spotlight and the effect of the light. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.  
Die cast aluminium body, powder coat painted.  
Integral heatsink. Integral premium driver.  
Low ripple output current <4% to assure camera and scanner friendly performance.  
Rotation 365°. Vertical adjustment 0-90°.  
Track mounted with 3-circuit adapter.



<b>Class of protection</b>	IP20, class I
<b>Colours</b>	White, black
<b>Weight total</b>	805g
<b>Reflector</b>	High purity aluminium
<b>Lifetime</b>	50.000h L80/B10 at Ta 25°C
<b>Mounting</b>	3-circuit universal adaptor
<b>Voltage</b>	220-240V 50/60hz
<b>Qty per MCB</b>	Max 34pcs/MCB 16A type B
<b>Ripple out. current</b>	< 4%. Flicker-free performance
<b>Colour consistency</b>	3 SDCM
<b>Photobiological safety</b>	RG1
<b>Design</b>	Jesper Ståhl
<b>Dimming</b>	Not dimmable



- White
- Black

# MOCCA S PRO

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																				
LIGHTSOURCE					LUMINAIRE			ART. No.																																																																																					
WARM WHITE 3000K (930)																																																																																													
MOCCA S Pro 1500lm SP 930	Spot 15°	3000K	92	1815	13W	1605	116	<b>222110</b>	<b>222114</b>																																																																																				
MOCCA S Pro 1500lm ME 930	Medium 25°	3000K	92	1815	13W	1605	116	<b>222111</b>	<b>222115</b>																																																																																				
MOCCA S Pro 1500lm FL 930	Flood 40°	3000K	92	1815	13W	1605	116	<b>222112</b>	<b>222116</b>																																																																																				
MOCCA S Pro 2500lm SP 930	Spot 15°	3000K	92	3070	23W	2710	114	<b>222210</b>	<b>222214</b>																																																																																				
MOCCA S Pro 2500lm ME 930	Medium 25°	3000K	92	3070	23W	2710	114	<b>222211</b>	<b>222215</b>																																																																																				
MOCCA S Pro 2500lm FL 930	Flood 40°	3000K	92	3070	23W	2710	114	<b>222212</b>	<b>222216</b>																																																																																				
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> </tr> <tr> <th colspan="2"></th> <th>1500lm</th> <th>2500lm</th> <th colspan="2"></th> <th>1500lm</th> <th>2500lm</th> <th colspan="2"></th> <th>1500lm</th> <th>2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>7998</td> <td>13507</td> <td>1</td> <td>0,41</td> <td>5252</td> <td>8867</td> <td>1</td> <td>0,74</td> <td>2910</td> <td>4913</td> </tr> <tr> <td>2</td> <td>0,57</td> <td>1999</td> <td>3377</td> <td>2</td> <td>0,83</td> <td>1313</td> <td>2217</td> <td>2</td> <td>1,42</td> <td>727</td> <td>1228</td> </tr> <tr> <td>3</td> <td>0,85</td> <td>889</td> <td>1501</td> <td>3</td> <td>1,23</td> <td>587</td> <td>985</td> <td>3</td> <td>2,18</td> <td>323</td> <td>546</td> </tr> <tr> <td>4</td> <td>1,13</td> <td>500</td> <td>844</td> <td>4</td> <td>1,65</td> <td>328</td> <td>554</td> <td>4</td> <td>2,91</td> <td>182</td> <td>307</td> </tr> </tbody> </table>										Spot				Medium				Flood						1500lm	2500lm			1500lm	2500lm			1500lm	2500lm	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	7998	13507	1	0,41	5252	8867	1	0,74	2910	4913	2	0,57	1999	3377	2	0,83	1313	2217	2	1,42	727	1228	3	0,85	889	1501	3	1,23	587	985	3	2,18	323	546	4	1,13	500	844	4	1,65	328	554	4	2,91	182	307
Spot				Medium				Flood																																																																																					
		1500lm	2500lm			1500lm	2500lm			1500lm	2500lm																																																																																		
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																		
1	0,28	7998	13507	1	0,41	5252	8867	1	0,74	2910	4913																																																																																		
2	0,57	1999	3377	2	0,83	1313	2217	2	1,42	727	1228																																																																																		
3	0,85	889	1501	3	1,23	587	985	3	2,18	323	546																																																																																		
4	1,13	500	844	4	1,65	328	554	4	2,91	182	307																																																																																		
<p><b>3000K 930</b> Spectral power distributions</p>																																																																																													
NEUTRAL WHITE 4000K (940)																																																																																													
MOCCA S Pro 1500lm SP 940	Spot 15°	4000K	92	1740	13W	1530	111	<b>222150</b>	<b>222154</b>																																																																																				
MOCCA S Pro 1500lm ME 940	Medium 25°	4000K	92	1740	13W	1530	111	<b>222151</b>	<b>222155</b>																																																																																				
MOCCA S Pro 1500lm FL 940	Flood 40°	4000K	92	1740	13W	1530	111	<b>222152</b>	<b>222156</b>																																																																																				
MOCCA S Pro 2500lm SP 940	Spot 15°	4000K	92	2920	23W	2570	109	<b>222250</b>	<b>222254</b>																																																																																				
MOCCA S Pro 2500lm ME 940	Medium 25°	4000K	92	2920	23W	2570	109	<b>222251</b>	<b>222255</b>																																																																																				
MOCCA S Pro 2500lm FL 940	Flood 40°	4000K	92	2920	23W	2570	109	<b>222252</b>	<b>222256</b>																																																																																				
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> </tr> <tr> <th colspan="2"></th> <th>1500lm</th> <th>2500lm</th> <th colspan="2"></th> <th>1500lm</th> <th>2500lm</th> <th colspan="2"></th> <th>1500lm</th> <th>2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>7626</td> <td>12809</td> <td>1</td> <td>0,41</td> <td>5006</td> <td>8409</td> <td>1</td> <td>0,74</td> <td>2774</td> <td>4659</td> </tr> <tr> <td>2</td> <td>0,57</td> <td>1906</td> <td>3202</td> <td>2</td> <td>0,83</td> <td>1252</td> <td>2102</td> <td>2</td> <td>1,42</td> <td>694</td> <td>1165</td> </tr> <tr> <td>3</td> <td>0,85</td> <td>847</td> <td>1423</td> <td>3</td> <td>1,23</td> <td>556</td> <td>934</td> <td>3</td> <td>2,18</td> <td>308</td> <td>518</td> </tr> <tr> <td>4</td> <td>1,13</td> <td>477</td> <td>801</td> <td>4</td> <td>1,65</td> <td>313</td> <td>526</td> <td>4</td> <td>2,91</td> <td>173</td> <td>291</td> </tr> </tbody> </table>										Spot				Medium				Flood						1500lm	2500lm			1500lm	2500lm			1500lm	2500lm	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	7626	12809	1	0,41	5006	8409	1	0,74	2774	4659	2	0,57	1906	3202	2	0,83	1252	2102	2	1,42	694	1165	3	0,85	847	1423	3	1,23	556	934	3	2,18	308	518	4	1,13	477	801	4	1,65	313	526	4	2,91	173	291
Spot				Medium				Flood																																																																																					
		1500lm	2500lm			1500lm	2500lm			1500lm	2500lm																																																																																		
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																		
1	0,28	7626	12809	1	0,41	5006	8409	1	0,74	2774	4659																																																																																		
2	0,57	1906	3202	2	0,83	1252	2102	2	1,42	694	1165																																																																																		
3	0,85	847	1423	3	1,23	556	934	3	2,18	308	518																																																																																		
4	1,13	477	801	4	1,65	313	526	4	2,91	173	291																																																																																		
<p><b>4000K 940</b> Spectral power distributions</p>																																																																																													

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.